

INTERCHANGE TABLES

Unsealed Cam Followers

Regular Stud • Unsealed

SMITH®	McGill	RBC	Torrington
CR - 1/2-A	CF - 1/2-N	—	CR - 8
CR - 1/2	CF - 1/2	S - 16	CR - 8-1
CR - 9/16	CF - 9/16	S - 18	—
CR - 5/8-A	CF - 5/8-N	—	CR - 10
CR - 5/8	CF - 5/8	S - 20	CR - 10-1
CR - 11/16	CF - 11/16	S - 22	—
CR - 3/4	CF - 3/4	S - 24	CR - 12
CR - 7/8	CF - 7/8	S - 28	CR - 14
CR - 1	CF - 1	S - 32	CR - 16
CR - 1 1/8	CF - 1 1/8	S - 36	CR - 18
CR - 1 1/4	CF - 1 1/4	S - 40	CR - 20
CR - 1 3/8	CF - 1 3/8	S - 44	CR - 22
CR - 1 1/2	CF - 1 1/2	S - 48	CR - 24
CR - 1 5/8	CF - 1 5/8	S - 52	CR - 26
CR - 1 3/4	CF - 1 3/4	S - 56	CR - 28
CR - 1 7/8	CF - 1 7/8	S - 60	CR - 30
CR - 2	CF - 2	S - 64	CR - 32
CR - 2 1/4	CF - 2 1/4	S - 72	CR - 36
CR - 2 1/2	CF - 2 1/2	S - 80	CR - 40
CR - 2 3/4	CF - 2 3/4	S - 88	CR - 44
CR - 3	CF - 3	S - 96	CR - 48
CR - 3 1/4	CF - 3 1/4	S - 104	CR - 52
CR - 3 1/2	CF - 3 1/2	S - 112	CR - 56
CR - 4	CF - 4	S - 128	CR - 64
CR - 5	CF - 5	S - 160	CR - 80
CR - 6	CF - 6	S - 192	CR - 96

Heavy Stud • Unsealed

SMITH®	McGill	RBC
HR - 1/2	CFH - 1/2	H-16
HR - 5/8	CFH - 5/8	H-20
HR - 3/4	CFH - 3/4	H-24
HR - 7/8	CFH - 7/8	H-28
HR - 1	CFH - 1	H-32
HR - 1 1/8	CFH - 1 1/8	H-36
HR - 1 1/4	CFH - 1 1/4	H-40
HR - 1 3/8	CFH - 1 3/8	H-44
HR - 1 1/2	CFH - 1 1/2	H-48
HR - 1 5/8	CFH - 1 5/8	H-52
HR - 1 3/4	CFH - 1 3/4	H-56
HR - 1 7/8	CFH - 1 7/8	H-60
HR - 2	CFH - 2	H-64
HR - 2 1/4	CFH - 2 1/4	H-72
HR - 2 1/2	CFH - 2 1/2	H-80
HR - 2 3/4	CFH - 2 3/4	H-88
HR - 3	CFH - 3	H-96
HR - 3 1/4	CFH - 3 1/4	H-104
HR - 3 1/2	CFH - 3 1/2	H-112
HR - 4	CFH - 4	H-128

Yoke Roller • Unsealed

SMITH®	McGill	RBC	Torrington
YR - 3/4	CYR - 3/4	Y-24	YCR - 12
YR - 7/8	CYR - 7/8	Y-28	YCR - 14
YR - 1	CYR - 1	Y-32	YCR - 16
YR - 1 1/8	CYR - 1 1/8	Y-36	YCR - 18
YR - 1 1/4	CYR - 1 1/4	Y-40	YCR - 20
YR - 1 3/8	CYR - 1 3/8	Y-44	YCR - 22
YR - 1 1/2	CYR - 1 1/2	Y-48	YCR - 24
YR - 1 5/8	CYR - 1 5/8	Y-52	YCR - 26
YR - 1 3/4	CYR - 1 3/4	Y-56	YCR - 28
YR - 1 7/8	CYR - 1 7/8	Y-60	YCR - 30
YR - 2	CYR - 2	Y-64	YCR - 32
YR - 2 1/4	CYR - 2 1/4	Y-72	YCR - 36
YR - 2 1/2	CYR - 2 1/2	Y-80	YCR - 40
YR - 2 3/4	CYR - 2 3/4	Y-88	YCR - 44
YR - 3	CYR - 3	Y-96	YCR - 48
YR - 3 1/4	CYR - 3 1/4	Y-104	YCR - 52
YR - 3 1/2	CYR - 3 1/2	Y-112	YCR - 56
YR - 4	CYR - 4	Y-128	YCR - 64
YR - 5	CYR - 5	Y-160	YCR - 80
YR - 6	CYR - 6	Y-192	YCR - 96

Optional Features	SMITH®	McGill	RBC	Torrington
Hex-Drive	Add Suffix "B"	Add Suffix "B"	Add Suffix "W"	Add Prefix "B"
Eccentric	Add Suffix "E"	Add Suffix "E"	Add Suffix "X"	Add Prefix "E"
Crowned O.D.	Add Suffix "C"	Add Prefix "C"	Add Prefix "C"	Add Prefix "C"
Thrust Seal	Add Suffix "L"	—	Replace "S" with "L"	—

INTERCHANGE TABLES

Sealed Cam Followers

Regular Stud • Sealed

SMITH®	McGill	RBC	Torrington
CR - 1/2-AX	CF - 1/2-N-S	---	CRS - 8
CR - 1/2-X	CF - 1/2-S	S - 16 -S	CRS - 8-1
CR - 9/16-X	CF - 9/16-S	S - 18 -S	---
CR - 5/8-AX	CF - 5/8-N-S	---	CRS - 10
CR - 5/8-X	CF - 5/8-S	S - 20 -S	CRS - 10-1
CR - 11/16-X	CF - 11/16-S	S - 22 -S	---
CR - 3/4-X	CF - 3/4-S	S - 24 -S	CRS - 12
CR - 7/8-X	CF - 7/8-S	S - 28 -S	CRS - 14
CR - 1-X	CF - 1 -S	S - 32 -S	CRS - 16
CR - 1 1/8-X	CF - 1 1/8-S	S - 36 -S	CRS - 18
CR - 1 1/4-X	CF - 1 1/4-S	S - 40 -S	CRS - 20
CR - 1 3/8-X	CF - 1 3/8-S	S - 44 -S	CRS - 22
CR - 1 1/2-X	CF - 1 1/2-S	S - 48 -S	CRS - 24
CR - 1 5/8-X	CF - 1 5/8-S	S - 52 -S	CRS - 26
CR - 1 3/4-X	CF - 1 3/4-S	S - 56 -S	CRS - 28
CR - 1 7/8-X	CF - 1 7/8-S	S - 60 -S	CRS - 30
CR - 2-X	CF - 2 -S	S - 64 -S	CRS - 32
CR - 2 1/4-X	CF - 2 1/4-S	S - 72 -S	CRS - 36
CR - 2 1/2-X	CF - 2 1/2-S	S - 80 -S	CRS - 40
CR - 2 3/4-X	CF - 2 3/4-S	S - 88 -S	CRS - 44
CR - 3-X	CF - 3 -S	S - 96 -S	CRS - 48
CR - 3 1/4-X	CF - 3 1/4-S	S - 104-S	CRS - 52
CR - 3 1/2-X	CF - 3 1/2-S	S - 112-S	CRS - 56
CR - 4-X	CF - 4 -S	S - 128-S	CRS - 64
CR - 5-X	CF - 5 -S	S - 160-S	CRS - 80
CR - 6-X	CF - 6 -S	S - 192-S	CRS - 96

Heavy Stud • Sealed

SMITH®	McGill	RBC
HR - 1/2-X	CFH - 1/2-S	H-16 -S
HR - 5/8-X	CFH - 5/8-S	H-20 -S
HR - 3/4-X	CFH - 3/4-S	H-24 -S
HR - 7/8-X	CFH - 7/8-S	H-28 -S
HR - 1-X	CFH - 1 -S	H-32 -S
HR - 1 1/8-X	CFH - 1 1/8-S	H-36 -S
HR - 1 1/4-X	CFH - 1 1/4-S	H-40 -S
HR - 1 3/8-X	CFH - 1 3/8-S	H-44 -S
HR - 1 1/2-X	CFH - 1 1/2-S	H-48 -S
HR - 1 5/8-X	CFH - 1 5/8-S	H-52 -S
HR - 1 3/4-X	CFH - 1 3/4-S	H-56 -S
HR - 1 7/8-X	CFH - 1 7/8-S	H-60 -S
HR - 2-X	CFH - 2 -S	H-64 -S
HR - 2 1/4-X	CFH - 2 1/4-S	H-72 -S
HR - 2 1/2-X	CFH - 2 1/2-S	H-80 -S
HR - 2 3/4-X	CFH - 2 3/4-S	H-88 -S
HR - 3-X	CFH - 3 -S	H-96 -S
HR - 3 1/4-X	CFH - 3 1/4-S	H-104 -S
HR - 3 1/2-X	CFH - 3 1/2-S	H-112 -S
HR - 4-X	CFH - 4 -S	H-128 -S

Yoke Roller • Sealed

SMITH®	McGill	RBC	Torrington
YR - 3/4-X	CYR - 3/4-S	Y-24 -S	YCRS - 12
YR - 7/8-X	CYR - 7/8-S	Y-28 -S	YCRS - 14
YR - 1-X	CYR - 1 -S	Y-32 -S	YCRS - 16
YR - 1 1/8-X	CYR - 1 1/8-S	Y-36 -S	YCRS - 18
YR - 1 1/4-X	CYR - 1 1/4-S	Y-40 -S	YCRS - 20
YR - 1 3/8-X	CYR - 1 3/8-S	Y-44 -S	YCRS - 22
YR - 1 1/2-X	CYR - 1 1/2-S	Y-48 -S	YCRS - 24
YR - 1 5/8-X	CYR - 1 5/8-S	Y-52 -S	YCRS - 26
YR - 1 3/4-X	CYR - 1 3/4-S	Y-56 -S	YCRS - 28
YR - 1 7/8-X	CYR - 1 7/8-S	Y-60 -S	YCRS - 30
YR - 2-X	CYR - 2 -S	Y-64 -S	YCRS - 32
YR - 2 1/4-X	CYR - 2 1/4-S	Y-72 -S	YCRS - 36
YR - 2 1/2-X	CYR - 2 1/2-S	Y-80 -S	YCRS - 40
YR - 2 3/4-X	CYR - 2 3/4-S	Y-88 -S	YCRS - 44
YR - 3-X	CYR - 3 -S	Y-96 -S	YCRS - 48
YR - 3 1/4-X	CYR - 3 1/4-S	Y-104-S	YCRS - 52
YR - 3 1/2-X	CYR - 3 1/2-S	Y-112-S	YCRS - 56
YR - 4-X	CYR - 4 -S	Y-128-S	YCRS - 64
YR - 5-X	CYR - 5 -S	Y-160-S	YCRS - 80
YR - 6-X	CYR - 6 -S	Y-192-S	YCRS - 96

Optional Features	SMITH®	McGill	RBC	Torrington
Hex-Drive	Add Suffix "B"	Add Suffix "B"	Add Suffix "W"	Add Prefix "B"
Eccentric	Add Suffix "E"	Add Suffix "E"	Add Suffix "X"	Add Prefix "E"
Crowned O.D.	Add Suffix "C"	Add Prefix "C"	Add Prefix "C"	Add Prefix "C"
Thrust Seal	Add Suffix "L"	-	Replace "S" with "L"	-